




Swing Check Valve - Grooved

SCG

Technical Features

- Sizes available (Nominal) : DN50/2", DN65/2½", DN80/3", DN100/4", DN150/6", DN200/8", DN250/10" & DN300/12"
- Pressure data :
Working Pressure : 21 bar (300 psi).
- Working Temperature : 0.0°C to 80.0°C
- Seat : Bronze
- Clapper : EPDM coated ductile iron
- Finish : Fusion bonded epoxy coated internal and external or painting according to request.
- Connections : Grooved joint dimensions are made in accordance with metric or AWWA C806.



Check Valves

Swing Check Valve - Grooved - SCG

Physical Data

Nominal Pipe Size		Dimensions (mm)					Reference	Weight (kg)
Metric	inch	L	D1	D2	b	c		
DN50	2"	172	57.2	60.3	7.9	15.9	SCG-0200	3.3
DN65	2½"	184	69.1	73.0	7.9		SCG-0250-073	3.6
			72.3	76.1			SCG-0250-076	
DN80	3"	197	84.9	88.9	7.9	SCG0-0300	4.6	
DN100	4"	206	110.1	114.3	9.5	19.1	SCG-0400	7.44
DN150	6"	325	160.9	165.1	9.5		SCG-0600-165	16.2
			164.0	168.3			SCG-0600-168	
DN200	8"	372	214.4	219.1	11.1	SCG-0800	26.9	
DN250	10"	457	268.3	273	12.7	SCG-1000	51.9	
DN300	12"	535	318.3	323.9		SCG-1200	75.6	

* Not UL or FM

Swing Check Valve - Grooved - SCG

Materials List

Item	Part Name	Material	ASTM Specification
1	Valve Body	Ductile Iron	ASTM A 536 Gr. 65-45-12
2	Hinge Pin	Stainless Steel	AISI 420
3	Spring	Stainless Steel	AISI 304
4	Spring Washer	Stainless Steel	AISI 304
5	Disc	DN50-DN100 Stainless Steel DN150-DN300 Ductile Iron	AISI 304 ASTM A 536 Gr. 65-45-12
6	Disc Sealing Ring	EPDM	Commercial
7	Seat Ring	Bronze	ASTM B62 C83600
8	Plug	Malleable Iron - Galvanised	
9	Bushing	Bronze	ASTM B62 C83600

