


50 Litre AFFF Foam Mobile Fire Extinguisher

- Robust
- For professional use in harsh environments



A high quality and robust mobile 50 litre AFFF foam extinguisher for professional use in harsh environments

Extinguishing medium

AFFF foam

Foam cylinder

315mm Ø x 2mm wall thickness
64 litre capacity
Stainless steel SS304
Welded to EN 288 & 1418
Test pressure (hydraulic) 30 bar
PED approved **CE**

Propellant

Nitrogen N₂

Propellant cylinder

3 litre external
T PED certified
Chrome molybdenum carbon EN1964-1
Brass safety valve, handwheel operated

Painting

Epoxy-polyester powder
Resistant to ultraviolet
Cylinders Red to RAL 3000
Frame Yellow to RAL 1003

Discharge hose

5m EPDM rubber flexible hose with swivel coupling
Fine control discharge nozzle

Filling cap

Material: Brass 100mm (4") full opening
Ø 95mm
Pressure gauge
Safety valve set to 24 ± 2 bar
Vent valve for pressure release

Frame

Welded steel "wrap around" frame
300mm Ø rubber rimmed wheels

Labelling


English/Arabic or English only

Angus Fire use Nitrogen (N₂), an environmentally neutral gas, as a propellant for their powder and foam mobiles:

- Nitrogen pressures are lower than Carbon Dioxide at high temperatures.
- Carbon Dioxide (CO₂) cools rapidly when released and can freeze water based foams.
- Nitrogen has an ozone depletion count of zero.


	Organic solid materials, wood rubber, textiles etc.
	Inflammable liquids, gasoline, oil etc.

	Temperature range: -30°C to +60°C Operating pressure: 13 bar @ 20°C nominal
	Jet length: ~ 8m Discharge time: ~ 46 seconds
	Filled weight: 84 Kg Packed volume: 0.30 cum
	Width: 455mm Depth: 550mm Height: 1145mm




50 Litre AFFF Foam Mobile Fire Extinguisher

Corrosion often occurs where the support frame is welded to the cylinder causing it to be unsafe. Angus Fire mobiles use a wrap around frame to support the cylinder. During maintenance the frame can be removed for servicing or repair.



A swivel is fitted as standard on all Angus Fire mobiles between the discharge hose and the nozzle. When the coiled hose is unwound the hose can un-twist leaving the nozzle free to direct the jet.



Options:

- Dust cover
- Extra length discharge hose 7.5m or 10m
- Rigid 2m helicopter lance
- CO₂ propellant in place of N₂ Teflon foil bursting disc
- MED Approval



The full range of Angus mobile extinguishers includes:

- 50 l; 100 l AFFF Foam
- 50 kg; 75 kg; 100 kg ABC powder
- 35 kg; 50 kg; 70 kg Monnex™ powder
- 10 kg; 20 kg; 30 kg; 50 kg CO₂

INTERNATIONAL SALES

Angus Fire Ltd
 Angus House, Haddenham Business Park,
 Pegasus Way, Haddenham, Aylesbury, HP17 8LB, UK
 Tel: +44 (0)1844 293600 • Fax: +44 (0)1844 293664

UK SALES

Angus Fire Ltd
 Station Road, Bentham, Lancaster, LA2 7NA, UK
 Tel: +44 (0)1524 264000 • Fax: +44 (0)1524 264180

Angus Fire operates a continuous programme of product development. The right is therefore reserved to modify any specification without prior notice and Angus Fire should be contacted to ensure that the current issues of all technical data sheets are used.