



STRIKE FIRST
FIRE EXTINGUISHERS



WATER



Meets or exceeds:
ANSI/UL 154 & 711
English / Spanish labels



Meets or exceeds:
CAN/ULC-S503 & S508
English / French labels

Built tough and easy to service

STRIKE FIRST
Water fire extinguishers
are designed for:



CLASS A
wood, paper, cloth

- Polished stainless steel cylinder complete with protective skirt
- Chrome-plated solid brass valve
- Waterproof stainless steel gauge
- Stainless steel handles and siphon tube
- Oversized stainless steel pull pin with retaining strap for easier and faster activation
- Colour and bar-coded labels for accurate service
- Schrader valve for pressurizing

Complies with NFPA 10 Standard

Meets D.O.T. Requirements

Temperature range: 40°F to 120°F (4°C to 49°C)

5 Year Warranty



| CAPACITY | 2.4 gallons (9 litres) |
|------------------|------------------------|
| UL Model No. | SF-PW250 |
| ULC Model No. | WBDL-PW250 |
| UL Rating | 2-A |
| ULC Rating | 2-A |
| Range | 40 ft (12.2 m) |
| Discharge Time | 40 sec |
| PSI | 100 |
| Height | 25" (63.5 cm) |
| Width | 8 3/4" (22 cm) |
| Diameter | 7 1/8" (18 cm) |
| Weight | 7.9 lb (3.6 kg) |
| Standard Bracket | Wall |

The STRIKE FIRST water extinguisher is an ideal choice for Class A fire hazards. The powerful stream of water allows it to reach areas other extinguishers cannot.

An effective extinguisher for Class A fires in areas such as warehouse, agriculture and industrial locations.



777 Tapscott Road
Scarborough
Ontario, Canada M1X 1A2

P 416 299-7767
TF 1 888 575-1132
F 416 299-8039
TF 1 888 575-1134

E info@strike-first.com
www.strike-first.com